



DO NOT use this machine unless you have received proper instruction and have been qualified in its safe use.



Safety glasses must be worn at all times in work areas.



Long and loose hair must be contained or constrained.



Appropriate footwear with substantial uppers must be worn.



Close fitting, protective clothing or a workshop apron is encouraged.



Rings and jewellery must not be worn.



Hearing protection may be required for some drilling operations.

PRE-OPERATIONAL SAFETY CHECKS

1. Ensure no slip/trip hazards are present in workspaces and walkways.
2. Check that all guards are in position.
3. Ensure hydraulic damping mechanism functions.
4. Check that the blade is in good condition.
5. Ensure that blade speed, blade tension and blade tracking are properly adjusted.
6. Check coolant delivery system to allow for sufficient flow of coolant.
7. Locate and ensure you are familiar with the operation of the ON/OFF starter and E-Stop (if fitted).
8. Faulty equipment must not be used. Immediately report suspect machinery.

OPERATIONAL SAFETY CHECKS

1. Lift the head of unit up and lock it in the upward position.
2. Set the angle of the vice, or check it to ensure its squareness.
3. Clamp work piece firmly into the vice. Long material must be supported.
4. Adjust blade guards to cover unused portion of blade.
5. Ensure hands are away from the blade, and then turn the machine on.
6. Allow the upper head assembly to come down slowly until the teeth are cutting the material.
7. Keep hands away from the point of operation during cutting.
8. Turn off the machine and bring it to a complete standstill if the blade is to be lifted out of an uncompleted or jammed cut.
9. Stop the machine and bring it to a complete standstill before removing scrap pieces from the vice area or making adjustments.
10. Stop the saw immediately if the blade develops a 'click'. Report it to your teacher.
11. Ensure the cutting head is locked in the upward position before removing work piece from vice.

HOUSEKEEPING

1. Switch off the saw and reset all guards to a fully closed position.
2. Leave the machine in a safe, clean and tidy state.

FORBIDDEN

- Pushing down on the cutting head while cutting
- Leaving the machine running unattended